



## M22 A HPA

Newest product of the HPA family for high quality finish and great comfort of use .

Features	Benefits
New ergonomics and body design Reduced trigger effort	The gun is part of the operator's arm who can focus on the application and the spraying movement for an improved quality
Unique aircap design	Unsurpassed finish quality with perfectly balanced fan
Fine thread stuffing box	Fine control of the needle tightening torque for an improved sealing
E-Z adjust aircap	Allows adjustment without loosening the retaining ring
Reduced number of components	Easy maintenance



### SPECIFICATIONS

Sprayed materials	Varnishes, lacquers, stains, polyurethanes, two components
Body of the gun	Anodised forged aluminum
Max. air feeding pressure (bar)	6
Recommended Trigger air (bar)	2 - 3
Air consumption (m3/h)	23 - 29,7
Weight (with cup) (g)	980
Maximum Fluid Temperature (°C)	50
Transfer efficiency in % (EN 13966-1)	62 %
Nozzle	Inox
Needle	Stainless steel
Wetted parts	Stainless steel/aluminum

### FITTINGS

Fitting	Air Inlet	M 1/4" NPS (+ M 1/4" BSP)
	Fluid inlet (for SM6 suction cup 1l)	M 3/8" NPS

### CONFIGURATION OF THE M22 A HPA

Max Fluid viscosity in CA 4	Projector type	Tip	Fluid output (cc/mn)	Air consumption (m3/h)	Fan width at 20 cm (cm)	Cup	Part number
		Size (mm)					
< 20 s	12 EN 2	1,2	100	23	16	SM6 (1 L)	136.145.200
		1,5	223	27	26,5		136.145.211
		1,8	270	29,7	27		136.145.213

### SEAL KITS

Designation	Part number
Seal kit	129.130.901
Repair kit (includes the seal kit)	129.130.902