



02.75 Pump

To be used with medium viscosity products. This pump can feed one or several guns.



Features	Benefits
Compact design	Easily integrated into a finish workshop
Rugged - High sealing capacity with singlelip seal	Compatible with a wide range of materials
Available in stainless steel version	Compatible with water-based materials

SPECIFICATIONS

Compression ratio	1,8/1	
Fluid volume per cycle (cm ³)	85	
Number of cycles per litre of products	12	
Air consumption (m ³ /h) at 30 cycles/mn at 4 bar	2,1	
Fluid Output at 30 cycles/mn (l/mn)	2,6	
Free flow rate (L/mn)	5,1	
Max. air feeding pressure (bar)	6	
Maximum fluid pressure (bar)	10	
Maximum Fluid Temperature (°C)	60	
Sound level (dBA)	81	
Sealing Packings	Upper sealing	GT cartridge with polyethylene packing
	Lower sealing	Acetal resin seal
Weight (kg) - bare pump	5	
Wetted parts	Aluminum, stainless steel	
Height (cm)	41	
Width (cm) - 2 regulators	28	
Depth (cm)	17	

FITTINGS

Fitting	Air inlet (valve)	F 3/8" BSP
	Air outlet (atomization air)	M 1/4" NPS
	Fluid Inlet	M 18x125
	Fluid Outlet	M 3/8" NPS

CONFIGURATION OF THE 02.75 PUMP

Set-up	Suction rod	Drain rod	Atomization air regulator	Fluid pressure regulator	Pump output filter	Part number
Standard, bare	-	-	-	-	-	144.941.000
Standard, wall-mounted	x	-	x	x	-	151.760.200
Bare, stainless steel	-	-	-	-	-	144.940.000
Wall-mounted, stainless steel	x	-	x	x	-	151.761.200
Wall-mounted, stainless steel with 2 air regulator and 1 fluid regulator	x	-	x	x	-	151.761.400

SEAL KITS

Designation	Part number
Seal kit for 75 fluid section	144.941.490
Repair kit for 75 fluid section	144.941.495

Seal kit for 340-2 air motor

144.850.150