



## AIRLESS pump 40.50 - Stainless steel

*Ideal for feeding two guns*



Features	Benefits
Simple design , reduced number of spare parts	Easy maintenance
Large diameter suction rod and high compression ratio	Use with a large number of materials

### Specifications

Compression ratio	40/1	
Fluid volume per cycle (cm <sup>3</sup> )	100	
Number of cycles per litre of products	10	
Fluid Output at 30 cycles/mn (l/mn)	3	
Free flow rate (L/mn)	6	
Air consumption (m <sup>3</sup> /h) at 30 cycles/mn at 4 bar	43,2	
Max. air feeding pressure (bar)	6	
Maximum fluid pressure (bar)	240	
Maximum Fluid Temperature (°C)	60	
Sound level (dBA)	82	
Sealing Packings	Upper sealing	Polyfluid + PTFE G
	Lower sealing	GT sealing
Wetted parts	Stainless steel	
Weight (kg) - wall-mounted	22	
Height (cm)	80	
Width (cm)	40	
Depth (cm)	28	

Fitting	Air inlet (valve)	F 3/4" BSP
	Air outlet (option atomization air kit)	M 1/4" NPS
	Fluid Inlet	M 26 x 125
	Fluid output (filter)	M 1/2" JIC

### CONFIGURATION OF THE AIRLESS 40.50 PUMP - STAINLESS STEEL

Set-up	Suction rod	Drain rod	Fluid pressure regulator	Pump output filter	Part number
Wall mounted		-		-	151.785.100
Wall mounted	x		x		151.785.200
Cart-mounted		x		x	151.785.400

### ATOMIZATION AIR KIT WITH REGULATOR

Designation	Part number
Atomization air kit with regulator (for MVX200 spray guns)	151.740.200

### SEAL KITS

Designation	Part number
H50 GT seal kit	144.960.091

H50 GT repair kit	<b>144.960.096</b>
Seal kit for 2000-4 air motor	<b>146.270.990</b>
Repair kit for 2000-4 air motor	<b>146.270.996</b>