



## S3 A HPA

*Small HPA gun featuring comfort and precision.*

Features	Benefits
New ergonomics and body design	The gun is part of the operator's arm who can focus on the application and the spraying movement for an improved quality
Reduced air consumption	Energy savings
In-line air valve assembly	Fine adjustment and long lasting components
2 different projectors : GAM and GL	2 types of application possible : GAM (flat fan) and GL (special line round fan)
2 fingers trigger	Improved comfort for more productivity
E-Z adjust aircap	Allows adjustment without loosening the retaining ring
PEHD cup	Compatible with new future materials (water-based products, etc...)



### SPECIFICATIONS

<b>Sprayed materials</b>	Varnishes, lacquers, stains, polyurethanes, two components
<b>Body of the gun</b>	Forged polish aluminum
<b>Max. air feeding pressure (bar)</b>	6
<b>Recommended Trigger air (bar)</b>	3
<b>Air consumption (m3/h)</b>	8-11
<b>Weight (with cup) (g)</b>	595
<b>Maximum fluid pressure (bar)</b>	6
<b>Maximum Fluid Temperature (°C)</b>	50
<b>Nozzle</b>	Inox
<b>Needle</b>	Stainless steel
<b>Wetted parts</b>	Stainless steel/PeHD/Aluminum

<b>Fitting</b>	<b>Air Inlet</b>	M 1/4" NPS
	<b>Fluid inlet (suction cup)</b>	PEHD 0.25L

### CONFIGURATION OF THE J53P SPRAY GUN WITH NPS FITTINGS

Max Fluid viscosity in CA 4	Projector type	Cup	Tip	Fluid output (cc/mn)	Air consumption (m3/h)	Fan width at 20 cm (cm)	Part number
			Size (mm)				
			-				<b>136.150.200</b>
14-20 s	08 AM	PeHD (grey) 0.25L	0,8	80	8	10	<b>136.150.208</b>
20-30 s	10 AM		1,0	92	9	12	<b>136.150.209</b>
30-40 s	12 AM		1,2	131	10	17	<b>136.150.210</b>
30-40 s	15 AY		1,5	165	11	18	<b>136.150.211</b>

Designation	Part number
Seal kit	<b>129.150.901</b>
Repair kit (includes the seal kit)	<b>129.150.902</b>