



S3 G HPA

Small HPA gun featuring comfort and precision recommended for precise works and decoration.



Features	Benefits
New ergonomics and body design	The gun is part of the operator's arm who can focus on the application and the spraying movement for an improved quality
Reduced air consumption	Energy savings
In-line air valve assembly	Fine adjustment and long lasting components
2 different projectors : GAM and GL	2 types of application possible : GAM (flat fan) and GL (special line round fan)
1 finger trigger	For an improved application accuracy
E-Z adjust aircap	Allows adjustment without loosening the retaining ring
PEHD cup	Compatible with new future materials (water-based products, etc...)

SPECIFICATIONS

Sprayed materials	Varnishes, lacquers, stains, polyurethanes, two components
Body of the gun	Forged polish aluminum
Max. air feeding pressure (bar)	6
Recommended Trigger air (bar)	3
Air consumption (m3/h)	8-10
Weight (with cup) (g)	515
Maximum fluid pressure (bar)	6
Maximum Fluid Temperature (°C)	50
Nozzle	Inox
Needle	Stainless steel
Wetted parts	Stainless steel/PeHD/Aluminum

FITTINGS

Fitting	Air Inlet	M 1/4" NPS
	Fluid inlet (gravity cup)	PeHD 0.25L

CONFIGURATION OF THE S3 G HPA SPRAY GUN WITH NPS FITTINGS

Max Fluid viscosity in CA 4	Projector type	Cup	Tip	Fluid output (cc/mn)	Air consumption (m3/h)	Fan width at 20 cm (cm)	Part number
			Size (mm)				
			-				136.155.100
14-20 s	08 AM	PeHD 0,25L (grey)	0,8	74	8	15	136.155.108
20-30 s	10 AM		1,0	83	9	18	136.155.109
30-40 s	12 AM		1,2	92	10	20	136.155.110
20-30 s	10 PGL		1,0	83	8	8	136.155.107

SEAL KITS

Designation	Part number
Seal kit	129.150.901
Repair kit (includes the seal kit)	129.150.902